Appln No. 10/611,753 Response date April 24, 2006 Reply to Office Action of February 23, 2006

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1. (Original) A method for supporting a frac blender on a transport vehicle in a manner permitting the frac blender to be moved between an upper stowed position and a lower operating position along a linear, vertical path, the method comprising:
- a. securing a support frame having a vertical reach to a transport vehicle:
- b. mounting a lift member within the support frame for movement along the vertical reach;
 - c. mounting the frac blender on the lift member; and
- d. selectively driving the lift member between the upper and lower positions.
- 2. (Original) The method of claim 1, including the step of providing a slip connection between the drive system and the lift member.
- 3. (Original) The method of claim 1, including the step of providing a slip connection between the support member and the lift member.
- 4. (Original) A method for supporting a frac blender on a transport vehicle in a manner permitting the frac blender to be

Appln No. 10/611,753 Response date April 24, 2006 Reply to Office Action of February 23, 2006

moved between an upper stowed position and a lower operating position along a linear, vertical path, the method comprising:

- a. securing a support frame having a vertical reach to a transport vehicle, the support member having a vertically extending slide rail;
- b. mounting a lift member on the slide rail for movement along the vertical reach of the support frame;
 - c. mounting the frac blender on the lift member; and
- d. selectively driving the lift member between the upper and lower positions along the slide.
- 5. (Original) The method of claim 4, including the step of providing a slip connection between the drive system and the lift member.
- 6. (Original) The method of claim 4, including the step of providing a slip connection between the support member and the lift member.